Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Lubricants - Specialty Oils

Version: **503/05**

Valvoline™ Lawnmower oil

Valvoline Lawnmower Oil is a premium lubricant specially developed for use in all 4-cycle lawn mowers, rotary cultivators, small tractors, floor cleaning machines and other similar equipment operating in a high revving environment. This product keeps the engine clean and protects against wear and corrosion.

Approvals/Performancelevels

SAE 30
API SG/CD

Applications

Lawnmower Oil is designed for use in garden equipment as well as in professional park maintenance equipment like rotary cultivators. Virtually all equipment with small engines used in the forest, agriculture,and industry can be lubricated with this product.
At home, lawnmower oil can be used for lawnmowers, brushcutters, snowblowers, etc. Warehouse equipment like floor cleaning machines and waterpump engines can be lubricated with Valvoline Lawnmower oil.

Features and Benefits

Wear protection:
Strong oil film protects the engine against wear and corrosion.

Engine cleanliness:
Keeps the engine clean and in good condition.

Break Down resistance:
Thermal and Oxidation stable oil film.

ASHLAND

Product Information

A PRODUCT OF ASHLAND CONSUMER MARKETS, A COMMERCIAL UNIT OF ASHLAND INC.

Health and Safety
This product is not likely to present any significant health or safety hazards when used correctly in the right application. A Material and Safety Data Sheet (MSDS) is available on request via your local sales office or via the internet @ **http://msds.ashland.com**

Protect the Environment
Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Typical Properties
Typical property characteristics are based on current production. Whilst future production will conform to Valvoline specifications, variations in these characteristics may occur.

Lawnmower Oil	
SAE Viscosity Grade	30
Viscosity, mm^2/s @ 100 ºC. ASTM D-445	10.5
Viscosity, mm^2/s @ 40 ºC. ASTM D-445	83
Viscosity Index ASTM D-2270	112
TBN, mg KOH/g ASTM D-2896	9.0
Pour Point, ºC ASTM D-5950	-21
Specific Gravity @ 15.6°C. ASTM D-4052	0.885
Flash Point, COC, ºC. ASTM D-92	232

This information only applies to products manufactured in the following location(s): Europe

People Who Know Use Valvoline™
Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit **www.valvolineeurope.com**

Author:
AdG
Replaces – 503/04

*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2013, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.