

## Valvoline Performance Products – Tectyl

Version: TE040/01

# Tectyl™ Biocleaner

*Premium water-based and biodegradable cleaner*

**Tectyl Biocleaner** is a water-based, biodegradable cleaner intended for removal of synthetic, animal, vegetable and mineral oils, greases and coatings.

**Tectyl Biocleaner** can be used as to remove Tectyl corrosion preventative coatings.

**Tectyl Biocleaner** leaves a clean and smooth surface.

## Approvals/Performance levels

### **Tectyl Biocleaner**

For removal of synthetic, animal, vegetable and mineral oils, greases and coatings.

Removes Tectyl corrosion preventative coatings.

## Application

The dilution and the exposure time depend on the nature and degree of pollution, the processing temperature and the chosen application method.

Tectyl Biocleaner is intended to be diluted in water (25%) for removing wax and oil based Tectyl layers up to the use of pure product (100%) with other layers or contaminated areas.

For dilution de-mineralized or normal tap water can be used.

Apply Tectyl Biocleaner, let it soak for several minutes and then rinse thoroughly with clean water. When necessary, repeat the treatment and/or increase the dosage. The use of hot water and mechanical support (such as pressurized water) will increase the efficiency.

When applying for the first time it is advised to **test the product prior to use to prevent non intended paint removal**. Applicable concentration is depending on the application method and application area.

## Features and Benefits

### **Excellent performance**

Tectyl Biocleaner gives an excellent clean surface

### **Economical**

Because highly concentrated the Tectyl Biocleaner is economical in use.

### **Safe to use**

Tectyl Biocleaner is biodegradable

### **Widely applicable**

Tectyl Biocleaner can be used in high pressure cleaning, tank-cleaning and floor scrubbers

**Health and Safety**

For the health and safety related properties of this product reference is made to the Safety Data Sheet (SDS). A Safety Data Sheet is available on request via your local sales office or via the internet @ <http://msds.ashland.com>

**Protect the Environment**

Do not discharge into drains, soil or water.

**Storage**

Due to its composition Tectyl Biocleaner can be subject to postproduction viscosity changes during storage. Tectyl Biocleaner should be stored at temperatures between 10-35 °C. **DO NOT FREEZE Tectyl Biocleaner** Under proper storage conditions Tectyl Biocleaner can have a shelf life of 24 months minimum.

**Typical Properties**

Typical property characteristics are based on current production. Whilst future production will conform to Tectyl specifications, variations in these characteristics may occur.

Tectyl Biocleaner	
Appearance	Yellow
Density at 20°C [g/l]	+/- 1
pH	10
Dynamic Viscosity [mPa.s]	1
Volatile Organic Content (VOC) [g/l]	101,9
Mildly Alkaline	

**Trusted since 1930**

Since 1930, Tectyl™ protective coatings have been extending the operational life of cars, trucks, buses and other vehicles and equipment. The Tectyl name is synonymous with quality coatings that are easy to apply, long-lasting and easy to remove when no longer required.

For more information on Tectyl products, programs and services please visit [www.tectyl-europe.com](http://www.tectyl-europe.com)

**Available packaging**

Volume
20 liter pail

**Author:**

RdB, April 2015

**This information only applies to products manufactured in the following location(s):**  
**Europe**

\*Trademark owned by a third party ™ Trademark of Ashland or its subsidiaries, registered in various countries © 2015, Ashland

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty, or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which Ashland Inc. and its subsidiaries assume legal responsibility.